99-168417-15

A(iii) D21. P06 G02

BADI 97.09.02

34*SE* Ni

\*DE 19738368-AT

Act+A2, (2-D5B, 12-W7D) D(8-B) F(3-F)7 (G/2/N3) 2-A4B+

5.29 (20%) 00, B290 41.36.

97,00 02 97DE-1038368 (99) (3) 44 (C99B 67/20, A51K 7) 00, B(55D) 7.24, Charliston, Charles 36, Charling 1938, Charles (6), Charles 17.60.

Platelet cholesteric multilaver pigments for use in effect lacquers -

comprising light-absorbing pigment between two cholesteric layers (Ger)

C99-049418

Nadn: Dutu

SCHUHMACHER P. SCHNEIDER N. RICHTER V. KELLER H, BETTINGER G, BLASCHKA P, HEILMANN P. MEYER F

NOVELTY

A placelet-torm enolesteric multilayer pigment has layers A B/A2 where A and A are cholesteric layers and B is an intermediate layer partially or wholly absorbing the light transmitted by A and A\*

An INDEPENDENT CLAIM relates to the preparation of the pigment by depositing the layers simultaneously or sequentially on a carrier, hardening them, removing the carrier and pulverising the lavers

USE

The pigments are used as effect lacquers or inks and or are used on venicles, lei aire or sports goods, in optical elements such as polarisers or filters, in cosmetics, textiles, leather or jeweiry, in gitts, writing implements or spectacles, in building or in domestic or printed goods. They can also be used in forgery-proofing or security-marking of articles.

<u>ADVANTAGE</u>

Effect pigments are provided which do not suffer from the defects of prior art pigments such as poor coverage; they do not require additional pigments in the cholesteric matrix nor a coloured. background to show good absorption properties.

Layers A and A comprise in the hardened state (a) a cholesteric polymerisable monomer: (b) an achiral, nematic polymerisable monomer and a chiral compound; (c) a cholesteric, crosslinkable polymer; or (d) a cholesteric polymer in a polymerisable diluent, (e) a cholesteric polymer whose cholesteric phase can be frozen by rapid DE 19738368-A+

cooling below the  $T_a$ ,  $A^a$  and  $A^a$  can have the same or different optical properties (eg wavelength reflection) and the thickness of each is 0.5-20 (especially 2-4)  $\mu$ m. At and A<sup>2</sup> are typically based on liquid crystal monomers such as those of DE19602848 or are polycarbonates, polyesters or corpolyisocyanates

Intermediate layer (B) is 0.2-5 (especially 0.5-2.5) jum thick and the multilaver pigment has a diameter of 5-500 (especially 10-30) jum, while pigment (B) is an (in)organic, preferably black and/or magnetic. absorption pigment, optionally in a binder. Manufacture of the pigment involves deposition of the layers on a carrier by (air) doctor -, air knife-, squeeze-, impregnation-, roller-, gravure-, kiss-, cast-, sprayor spin-coating or by printing such as relief-, intaglio-, flexo- or offset-printing, especially by cast-coating or offset printing.

<u>EXAMPLE</u>

None given. (RB) (30pp1958DwgNo.0/0)

DE 19738368-A